

## Hexaplexer 906/1733/1940MHz

### Specifications :

Model No.	HT-HEXA-091721-SMA-F					
<b>Electrical characteristics</b>						
Item	Rx	Tx	Rx	Tx	Rx	Tx
Frequency(MHz)	906-913 MHz	951-958 MHz	1733-1755MHz	1828-1850MHz	1940-1965MHz	2130-2155MHz
Bandwidth(MHz)	7MHz	7MHz	22MHz	22MHz	25MHz	25MHz
Insertion loss	≤1.4dB	≤1.4dB	≤1.4dB	≤1.4dB	≤1.4dB	≤1.4dB
In-Band Ripple	≤1.0dB	≤1.0dB	≤1.0dB	≤1.0dB	≤1.0dB	≤1.0dB
Intersection suppression(MHz)	≥40@925MHz		≥40@1795MHz		≥40@2045MHz	
Isolation (dB)	≥80					
VSWR	≤1.25					
Input power (W)	50W/per port (average power)					
<b>Environment characteristics</b>						
Operation temperature	-20℃ ~ +55℃					
Relative humidity	5% - 95%					
<b>Mechanical characteristics</b>						
Connectors	SMA-F					
Net Weight (kg)	***					
Dimension, mm	162*115*70					

### Outline drawing :

